

# B Compact Tractor B2320/B2620/B2920



## Competitive Comparison

MODEL		Kubota B2320DT/ B2320HSD	John Deere JD2305	John Deere JD2320	Kubota B2620HSD	John Deere JD2520	New Holland T1110	Kubota B2920HSD		
Engine	Engine gross power	HP(kw)	23.0 (17.2)	24.0 (17.9)	24.0 (17.9)	26.0(19.4)	26.5 (19.8)	28.0 (20.9)	29.0 (21.6)	
	PTO power	HP(kw)	Gear 18.0 (13.4) / HSD 17 (12.7)	18.0 (13.4)	18.0 (13.4)	19.0 (14.2)	20.0 (14.9)	20.5 (15.3)	21.0 (15.7)	
	No. of cylinders		3	3	3	3	3	3	3	
	Total displacement	cu.in.(cm3)	61.1 (1001)	68.0 (1115)	68.0 (1115)	68.5 (1123)	81.2 (1331)	69.0 (1.1)	77.0 (1261)	
	Rated revolution		2800	3000	3000	2800	2600	3100	2800	
	Fuel tank capacity	gal.(l)	6.6 (2.5)	5.5 (21)	6.1 (23)	6.6 (25)	7.1 (27)	7.1 (26.9)	6.6 (25)	
	Double air cleaner		Standard	Standard	Standard	Standard	Standard	N/P	Standard	
Drive train	Transmission		Gear/HST	HST	HST	HST	HST	HST	HST	
	No. of traveling speeds		9F/3R / 3-Range	2-Range	2-Range	3-Range	2-Range	2-Range	3-Range	
	Max. traveling speed	mph(km/h)	11.2 (18.0) / 11.7 (18.9)	8.3 (13.3)	11.3 (18.2)	12.6 (20.2)	13.0 (20.9)	11.2 (18.1)	12.6 (20.2)	
	Brake		Multi-plate wet, disc	Wet, Disc	Wet, Disc	Multi-plate wet, disc	Wet, Disc	Wet, Disc	Multi-plate wet, disc	
	PTO clutch		Transmission driven with one way clutch / Live	Independent	Independent	Live	Independent	Independent	Live	
Tires	Farm	Front	6-12	N/A	N/A	7-12	N/A	N/P	7-12	
		Rear	9.5-16	N/A	N/A	11.2-16	N/A	N/P	11.2-16	
	Turf	Front	23 x 8.50-12	18x8.5-10	23x8.5-12	23x8.50-12	24x8.5-14	20x10.00-10	23x8.50-12	
		Rear	33 x 12.5-15	26x12.0-12	31x13.5-15	33x12.5-15	36x14.0-15	29x12.5-15	33x12.5-15	
	R4	Front	23 x 8.50 -12	18x8.5-10R4	23x8.5-12	23x8.50-12	23x8.5-12	20x10.00-10	23x8.50-12	
		Rear	12-16.5	26-12.0-12R4	12-16.5	12-16.5	14-17.5	29x12.5-15	12-16.5	
Hydraulic System	Pump capacity	gpm(l/min)	8.3 (31.4)	5.2 (19.7)	5.6 (21.2)	8.3 (31.4)	10.5 (39.6)	6.5 (24.6)	8.3 (31.4)	
	3-Point Hitch lift capacity @	lbs.(kg)	1058 (480)	701 (318)	1151 (522)	1058 (480)	1151 (522)	1000 (454)	1058 (480)	
	Front Loader valve & lever		Standard	Standard/ Optional	Standard	Standard	Standard	Optional	Standard	
	Power steering		Standard (Integral)	Standard (Hydraulic)	Standard (Hydraulic)	Standard (Integral)	Standard (Hydraulic)	Standard (Hydrostatic)	Standard (Integral)	
Others	Cruise Control		N/A / Standard	N/A	Standard	Standard	Standard	Optional	Standard	
	Toolbox		Standard	N/A	N/A	Standard	N/A	Standard	Standard	
Dimensions	Wheelbase	in.(mm)	61.5 (1563)	57.1 (1450)	63.0 (1600)	61.5 (1563)	65.2 (1655)	57.5 (1460)	61.5 (1563)	
	Tread	Front	in.(mm)	31.5 (800)	35.6 (905)	36.3 (923)	31.5 (800)	36.3 (923)	N/P	31.5 (800)
		Rear	in.(mm)	34.9-39.6 (886-1006)	35.3 (896)	37.0 (941)	35.0-41.9 (890-1064)	39.2 (995)	N/P	35.0-41.9 (890-1064)
	Min. ground clearance	in.(mm)	12.0 (305)	7.7 (195)	12.3 (313)	12.8 (352)	10.2 (260)	7.8 (197)	12.8 (325)	
	Min. turning radius w/ brake	ft.(m)	6.9 (2.1)	7.5 (2.3)	6.6 (2.0)	6.9 (2.1)	7.5 (2.3)	6.8 (2.0)	6.9 (2.1)	
	Weight (w/ROPS)	lbs.(kg)	1433 (650) / 1477 (670)	1451 (658)	1660 (753)	1554 (705)	1865 (846)	1492 (677)	1554 (705)	

N/A = Not Available  
N/P = Not Published

Smile  
on my mac