



TLB *Loader/Landscaper Tractors* B21



COMPETITIVE COMPARISON

FEATURE	KUBOTA B21TLB	ALAMOND BROS TLB-25	TERRAMITE T5C
ENGINE			
ENGINE	Kubota 3-Cylinder Diesel	Gas - Air cooled Robin EH65D optional (Kohler) CH20S	Kohler Command
Spark arrestor muffler	Standard	INA (Information Not Available)	INA
HP	21 Diesel	20.5 Gas Robin 20.0 Kohler (Optional)	20.0 Gas Kohler Command
Transmission	HST - Kubota	HST- Eaton	HST- Eaton
Range	3 Speed Low, Medium, High	Single speed	Single speed
Travel Speeds	Low 0 - 2.9 mph Medium 0- 5.0 mph High 0 - 11.0 mph	0 - 5.5 mph	0 - 5.0 mph
Differential (Rear)	Diff-Lock	Limited-slip	
HYDRAULICS			
Hyd. Pump	Open Center	Open Center	Open Center
Pump	Dual pumps	Single pump	Single pump
Total GPM	13.10	7.00	7.00
Loader/Backhoe	7.13	INA	INA
Power Steering	1.32	INA	INA
HST	4.60	INA	INA
Hyd/Trans. Oil cooler	Standard	INA	INA
Three Point Hitch	Standard	N/A	N/A
Cat I	Standard	N/A	
Lift Capacity (24" behind)	1,017 Lbs.	N/A	
BRAKES			
Brakes	Wet Disc	Dry Band type	Dry Band type
PTO			
Rear PTO	Live 540 rpm Standard	Not available	Not available
CAPACITIES			
Fuel Tank	6.3 gal. (Diesel)	12.0 gal. (Gas)	7.0 gal. (Gas)
Cooling System	0.9 gal.	INA	INA
Engine Oil	0.8 gal.	INA	INA
Transmission Hyd. Oil	7.3 gal.	10 gal.	7.0 gal.
MODEL	Kubota B21TLB	Alamond Bros TLB-220	Terramite T5C



TLB *Loader/Landscaper Tractors* B21



COMPETITIVE COMPARISON

FEATURE	KUBOTA B21TLB	ALAMOND BROS TLB-25	TERRAMITE T5C
LOADER			
Lift Capacity Lbs. (Bucket to full height)	926 Lb.	1,700 Lb.	1,700 Lb
Breakout Force	1,543 Lb.	2,600 Lb.	2,200 Lb.
Raise time to full height, seconds.	3	INA	INA
Dump angle	45 degrees	25 degrees	25 degrees
Rollback angle	40 degrees	40 degrees	35 degrees
Maximum lift height	88.8"	90"	82"
Digging Depth	6.3"	4.0"	INA
Self Leveling feature	Standard	N/A	N/A
Bucket	56" wide	56" wide	48"
TIRES			
Front	23 X 8.50 - 14 R4 Industrial	20.5 X 8.0 - 12 Rib type	23.0 x 8.0 x 12 (skid steer)
Rear	12.4-16 R4 Industrial	31 X 15.5 - 15 Bar Type	9.5 - 16 Super Sure Grip
Weight	3,988 Lbs. w/Std. Bucket and standard 16" Bkhoe bucket	3,470 Lbs. w/loader bucket and Std. 16" backhoe bucket	3,100 lbs.
BACKHOE			
Quick Attach system	Standard (No tools removal)	N/A	N/A
Digging depth	7.64' (2ft flat bottom)	7.6' (2 ft flat bottom)	8.3' INA for 2' flat bottom rating
Swing Arc	180 degrees	180 degrees	145 degrees
Loading Height	6' 8"	6' 4"	6'3"
Reach from swing pivot	121.3"	119"	132"
Digging Force/Bucket cyl.	3,110 Lbs.	2,875 Lbs.	3,100 Lbs.
Digging Force/Crowd (Dipper) cyl.	1,748 Lbs.	2,265 Lbs.	
Bucket Sizes available	10", 12", 16", 24" 30" and 36"	10", 12" 16" 18" and 24"	8", 12", 16", 20",24", 36"