


SPECIFICATIONS

| MODEL | | B21 | |
|----------------------------|--|----------------------------|---------------------------------------|
| Engine | Gross power (SAE) | HP (kW) | 21.0 (15.7) |
| | Net power (SAE) | HP (kW) | 19.0 (14.2) |
| | Total displacement | cu. in. (cm ³) | 61.1 cu. in. (1001) |
| | No. of cylinders | | 3 |
| | Rated speeds | | 2600 rpm |
| Transmission/Drive Train | Type | | HST (3 Range) |
| | No. of speeds | | Infinite |
| | Clutch | | Dry, Single |
| | Power Steering | | Integral |
| | Max. traveling speed | mph (km/h) | 11.1 (17.8) |
| | Shift lever position | | Seat side, right |
| PTO System | Max PTO Power | HP (kW) | 13.5 (10.0) |
| | Rear PTO | | 540 rpm, Live-continuous running |
| Hydraulic System | Type | | Open center/constant flow |
| | Pump capacity | gpm. (l/min) | 8.5 (32) |
| | Maximum Operating Pressure | | 2000 |
| | 3-Point Hitch Type | | Category I |
| | 3-Point Hitch lift capacity at 24 in. (610 mm) behind LP | lbs. (kg) | 1057 (479) |
| | Position control | | Standard |
| Dimensions & Weight | Fuel Tank Capacity | gal. (l) | 6.3 (24) |
| | Wheel Base | in. (mm) | 60.4 (1535) |
| | Front Tread | in. (mm) | 37.8 (960) |
| | Rear Tread | in. (mm) | 41.3 (1050) |
| | Weight with Loader, Backhoe and ROPS/FOPS | lbs. (kg) | 3836 (1740) |
| | Min. Turning Radius w/o brake | ft. (m) | 9.4 (2.85) |
| ROPS/FOPS | | | 4 Post, with retractable seat belt |
| Tire Size | Front | | 23X8.50-14 R4 (IND) |
| | Rear | | 12.4-16 R4 (IND) |
| Other Performance Features | Hood | | Slanted hard nose hood |
| | Frame | | Loader-integrated reinforced frame |
| | Brakes | | Wet Disc Brakes |
| | Seat | | Movable seat (Reinforced type) |
| | Steering Wheel | | Tilt steering wheel |
| | Muffler | | Muffler enclosed (w/spark arrestor) |
| | Pedals | | Hanging type pedals |
| | Deck | | Full-floating ISO-mounted Flat deck |

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.