



Compact Tractors

B2630/B3030



Competitive Comparison

MODEL			Kubota B2630HSD	John Deere 2520	Kiotti CK25HST	Mahindra 2310HST	New Holland TC26DA
Engine	Engine gross power	HP(kw)	26.0(19.4)	26.5(19.8)	25(18.7)	25(18.7)	26.0 (19.4)
	PTO power	HP(kw)	19.5(14.5)	20.5(15.3)	18(13.4)	20(15)	19.7 (14.7)
	No. of cylinders		3	3	3	3	3
	Total displacement	cu.in.(cm3)	68.5(1123)	81.2(1330)	79.3(1299)	79(1299)	69.0 (1.131)
	Fuel tank capacity	gal.(l)	8.1(31)	7.1(27)	7.9(30)	N/P	5.3 (20)
	Double air cleaner		Standard	Standard	N/P	N/P	Standard
Transmission	Type		HST (3 ranges)	HST (2 ranges)	HST (3 ranges)	HST (3 ranges)	HST (2 ranges)
	Max. traveling speed	mph(km/h)	13.4(21.5)	N/P	13.11(21.1)	N/P	N/P
	Brake		Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc
PTO	Live PTO		N/A	N/A	Standard	N/A	Standard
	Independent PTO		Standard	Standard	N/A	Standard	N/A
	Mid PTO		Standard	Standard	Optional	Standard	Standard
Tires	Farm	Front	7-12	N/P	7-14	N/P	16-21
		Rear	12.4-16	N/P	11.2-24	N/P	9.5-16
	Turf	Front	23X8.50-12	N/P	27x8.50-15	28x8.5-15	N/P
		Rear	13.6-16	N/P	41x14.00-20	41x14-20	N/P
	R4	Front	23X8.50-14	23x8.50-12	25x8.50-14	10x16.5	N/P
		Rear	12.4-16	36x14.00-17.5	15-19.5	43x16-20	N/P
Hydraulic System	Pump capacity	gpm(l/min)	5.6+4.2(21.2+16.0)	5.5+5.0(20.8+18.8)	12.7(48.1)	6.3+4.6(23.8+17.4)	5.4+3.0(19.8+11.4)
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.(kg)	1676(760)	1150(522)	1764(800)	2080(943)	1265(574)
	Position control		Standard	Standard	Standard	Standard	N/P
	Power steering		Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
3-Point Hitch	Telescopic lower link ends		Standard	N/P	Standard	N/P	N/P
	Lower link adjustment		Telescopic stabilizers	N/P	Telescopic stabilizers	N/P	N/P
	Lift rod adjustment		Ratchet	N/P	Crank	N/P	N/P
Cab	Availability		N/A	N/A	N/A	N/A	N/A
	Cup Holder		Standard	N/P	Standard	Standard	N/P



Compact Tractors

B2630/B3030



Competitive Comparison

Generals	Toolbox		Standard	N/P	N/P	Standard	N/P	
	Tilt steering wheel		Standard	N/P	Standard	Standard	N/P	
	Deluxe seat with armrest		Standard	N/P	N/P	N/P	N/P	
Dimensions	Wheelbase		in.(mm)	65.6(1666)	65.2(1655)	66.1(1680)	N/P	57.5 (1460)
	Tread	Front	in.(mm)	36.8(935)	32.7(830)	43.5(1105)	N/P	33.3 (846)
		Rear	in.(mm)	41.3(1050)	N/P	38.2-51.3(970-1302)	N/P	35.2 (895)
	Min. ground clearance		in.(mm)	14.6(370)	12.5(318.4)	13.82(351)	N/P	10.7 (273)
	Overall length w/3-Point Hitch		in.(mm)	99.2(2520)	N/P	122.2(3103)	114(2896)	106.3 (2700)
	Overall height		in.(mm)	78.6(1997)	N/P	96.8(2460)	N/P	81.2 (2063)
	Overall width		in.(mm)	53.8(1366)	N/P	54.6(1387)	60.2(1656)	44.7 (1135)
Weight (w/ROPS)		lbs.(kg)	1829(830)	1865(846)	3055(1386)	3064(1390)	1,600 (726)	

N/A = Not Available; N/P = Not Published

These comparison of specifications are based upon the most reliable data obtainable by Kubota at the time of publication.

Kubota reserves the right to change specifications without notice.

Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was being prepared.

It is correct to the best of our knowledge but due to technological developments it is subject to change without notice.



Smile
on my mac



Compact Tractors

B2630/B3030



Competitive Comparison

MODEL		Kubota B3030HSD	John Deere 3120	Kiotei CK30HST	New Holland TC29DA	Massey Ferguson 1429	
Engine	Engine gross power	HP(kw)	30.0(22.4)	29.5(22)	30.0(22.4)	29.0(21.6)	28.4(21.2)
	PTO power	HP(kw)	23.0(17.1)	22(16.4)	22.0(16.4)	23.6(17.6)	23.0(17.1)
	No. of cylinders		4	3	3	3	3
	Total displacement	cu.in.(cm3)	91.4(1498)	91.5(1500)	91.5(1500)	81.2(1330)	89.3(1450)
	Fuel tank capacity	gal.(l)	8.1(31)	13.5(51.1)	7.9 (30)	7.3(27.6)	7.9(30)
	Double air cleaner		Standard	Standard	N/P	Standard	N/P
Transmission	Type		HST (3 ranges)	E Hydro (3 ranges)	HST (3 ranges)	HST (3 ranges)	8F/8R Synchro
	Max. traveling speed	mph(km/h)	13.4(21.5)		13.11 (21.1)	15.6(25.1)	12.32(19.82)
	Brake		Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc
PTO	Live PTO		N/A	N/A	Standard	Standard	N/A
	Independent PTO		Standard	Standard	N/A	N/A	Standard
	Mid PTO		Standard	Optional	Optional	Standard	Optional
Tires	Farm	Front	7-12	7-14	7-14	7-14	N/P
		Rear	12.4-16	11.2-24	11.2-24	11.2-24	11.2-24
	Turf	Front	23X8.50-12	N/P	27x8.50-15	24X8.50-14	N/P
		Rear	13.6-16	N/P	41x14.00-20	13.6-16	N/P
	R4	Front	23X8.50-14	N/P	25x8.50-14	25X8.50-14	N/P
		Rear	12.4-16	N/P	15-19.5	15-19.5	N/P
Hydraulic System	Pump capacity	gpm(l/min)	5.2+3.9(19.7+14.8)	8.6+5.3(32.5+20.0)	12.7 (48.0)	7.1+5.1(27.0+19.3)	7.4+4.3(28+16.3)
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.(kg)	1676(760)	2200(999)	1764(800)	1638(743)	2756(1250)
	Position control		Standard	Standard	Standard	Standard	Standard
	Power steering		Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
3-Point Hitch	Telescopic lower link ends		Standard	N/P	Standard	Standard	Standard
	Lower link adjustment		Telescopic stabilizers	N/P	Telescopic stabilizers	Telescopic stabilizers	Telescopic stabilizers
	Lift rod adjustment		Ratchet	N/P	Crank	Crank	N/P
Cab	Availability		Optional	N/A	N/A	N/A	N/A
	Cup Holder		Standard	N/P	Standard	Standard	N/P



Compact Tractors

B2630/B3030



Competitive Comparison

General			Standard	N/P	N/P	Standard	N/P	
Toolbox			Standard	N/P	N/P	Standard	N/P	
Tilt steering wheel			Standard	N/P	Standard	Standard	N/P	
Deluxe seat with armrest			Standard	N/P	N/P	OPT	N/P	
Dimensions	Wheelbase	in.(mm)	65.6(1666)	68(1727)	66.1(1680)	63.0(1600)	68.5(1740)	
	Tread	Front	in.(mm)	36.8(935)	45.2(1079.5)	43.5(1105)	40.0-42.3(1016-1074)	42.9(1090)
		Rear	in.(mm)	41.3(1050)	N/P	41.3(1050)	42.8-47.9(1087-1217)	43.3-55.9(1100-1420)
	Min. ground clearance	in.(mm)	14.6(370)	11.4(290)	13.82(351)	14.0(355)	N/P	
	Overall length w/3-Point Hitch	in.(mm)	99.2(2520)	N/P	122.2(3103)	106.2(2700)	121.5(3085)	
	Overall height	in.(mm)	78.6(1997)	N/P	96.8(2460)	87.8(2231)	85.8(2180)	
	Overall width	in.(mm)	53.8(1366)	N/P	54.6(1387)	54.3(1377)	54.9(1395)	
Weight (w/ROPS)	lbs.(kg)	1895(860)	2900(1316)	3055(1386)	2480(1125)	2734(1240)		

N/A = Not Available; N/P = Not Published

These comparison of specifications are based upon the most reliable data obtainable by Kubota at the time of publication.

Kubota reserves the right to change specifications without notice.

Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was being prepared.

It is correct to the best of our knowledge but due to technological developments it is subject to change without notice.



Smile
on my mac