



SPECIFICATIONS

MODEL			B2630HSD	B3030HSD	B3030HSDC (cab)
Engine	Type		E-TVCS liquid cooled, 3-cylinder diesel		E-TVCS liquid cooled, 4-cylinder diesel
	Make, Model	HP (kW)	Kubota D1105-E2-D21	Kubota V1505-E2-D21	Kubota V1505-E2-D21-Q
	PTO Horsepower	HP (kW)	19.5 (14.5)	23.0 (17.1)	
	Engine gross horsepower	HP (kW)	26.0 (19.4)	30.0 (22.4)	
	Rated RPM		2800	2600	
	Bore and stroke	in. (mm)	3.1x3.1 (78x78.4)		
	Total displacement	cu.in. (cc)	68.5 (1123)	91.5 (1498)	
	Air Cleaner		Dual paper element		
	Lubrication		Forced lubrication		
	Cooling System		Pressurized radiator		
Radiator fan		Radial air flow			
Capacities	Fuel tank	gal. (l)	8.1 (31)		
	Cooling system	qts. (l)	4.2 (4.0)	4.7 (4.5)	4.5 (4.3)
	Engine oil	qts. (l)	3.2 (3.0)	4.3 (4.1)	
	Transmission case	gal. (l)	4.76 (18)		
Drive Train	Clutch		N/A		
	Transmission		HST (3 range)		
	Differential lock		Standard		
	Final drive		Spur gear		
	Brake		Multi-plate wet disc		
	PTO		Independent		
		Rear		540 rpm at 2768 engine rpm	540 rpm at 2592 engine rpm
	Mid		2542 rpm at 2800 engine rpm	2500 rpm at 2600 engine rpm	
Hydraulics	Type		Open center		
	Pump		Dual pump		
	Total pump output	gpm (l/min)	9.8 (37.2)	9.1 (34.5)	
	Hydraulic outlet		Front outlet, Rear outlet		
	3-point hitch		Category I		
	Hydraulic control system		Position control valve		
	Lift capacity (at lift point) (24 in. behind LP)	lbs. (kg)	2140 (970)		
		lbs. (kg)	1676 (760)		
Steering		Hydrostatic power steering			
Standard Tire Size	Front		'7-12		
	Rear		12.4-16		
Traveling Speeds (at rated engine rpm)	Forward	mph (km/h)	0-11.5 (0-18.6)	0-12.1 (0-19.5)	
	Reverse	mph (km/h)	0-9.2 (0-14.8)	0-9.6 (0-15.5)	
Dimensions	Overall length (w/o 3P)	in. (mm)	99.2 (2520)		103.9 (2640)
	Overall width (min. tread)	in. (mm)	53.8 (1366)		
	Wheelbase	in. (mm)	65.6 (1666)		
	Ground clearance	in. (mm)	14.6 (370)		
	Turning radius with brake	ft. (m)	6.9 (2.1)		
	Weight with ROPS	lbs. (kg)	1786 (810)	1852 (840)	2271 (1030)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.