


SPECIFICATIONS

MODEL		BX24	
Engine	Type	E-TVCS liquid cooled, 3-cylinder diesel	
	Make, Model	HP (kW)	Kubota D902
	PTO Horsepower	HP (kW)	17.7 (13.2)
	Engine gross horsepower	HP (kW)	23.0 (17.2)
	Rated RPM		3200
	Bore and stroke	in. (mm)	2.8 x 2.9 (72x73.6)
	Total displacement	cu.in. (cc)	54.8 (898)
	Air Cleaner		Dry paper dual element
	Lubrication		Forced lubrication
	Cooling System		Pressurized radiator
Radiator fan		Radial air flow	
Capacities	Fuel tank	gal. (l)	6.6 (25)
	Cooling system	qts. (l)	2.8 (2.7)
	Engine oil	qts. (l)	3.3 (3.1)
	Transmission case	gal. (l)	3.1 (11.6)
Drive Train	Clutch		N / A
	Transmission		HST (2 range)
	Differential lock		Standard
	Final drive		Spur gear
	Brake		Multi wet disc
	PTO		Hydraulic Independent
		Rear	
	Mid		2500 rpm at 3125 engine rpm
Hydraulics	Type		Open center
	Pump		Gear Type
	Total pump output	gpm (l/min)	6.3 (24.0)
	Hydraulic outlet		Block (Mid & Rear)
	3-point hitch		Category I
	Hydraulic control system		Quarter Inching Valve
	Lift capacity (at lift point)	lbs. (kg)	992 (450)
	(24 in. behind LP)	lbs. (kg)	661 (300)
Steering		Hydrostatic power steering	
Standard Tire Size	Front		18 x 8.50 - 10 Turf
	Rear		26 x 12.00 - 12 Turf
Traveling Speeds (at rated engine rpm)	Forward	mph (km/h)	0 - 8.1
	Reverse	mph (km/h)	0 - 6.2
Dimensions	Overall length (with 3P)	in. (mm)	95.5 (2425)
	Overall width (min. tread)	in. (mm)	32.3" (820)
	Wheelbase	in. (mm)	55.1 (1400)
	Ground clearance	in. (mm)	8.7 (220)
	Turning radius w/o brake	ft. (m)	7.5 (2.3)
	Weight with ROPS	lbs. (kg)	1542 (700)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

