

BX

BX2660

SPECIFICATIONS

Specifications

Model		BX2660	
Engine			
Type	Liquid-cooled, 3-cylinder diesel		
Model	Kubota D1005		
Engine gross HP at 3200 rpm	HP (kW)	25.5 (19.0)	
PTO horsepower at 3200 rpm	HP (kW)	19.5 (14.5)	
Displacement	cu.in. (cc)	61.1 (1001)	
Fuel tank capacity	gal. (ℓ)	6.6 (25)	
Drive train			
Transmission	HST, High-Low gear shift (2 forward / reverse)		
Drive method	2WD and 4WD selection		
Brakes	Wet disc		
PTO	Live independent, wet hydraulic clutch		
Rear	STD (540rpm)		
Mid	STD (2500rpm)		
Hydraulics			
Pump output	gpm (ℓ/min.)	6.3 (24)	
3-point hitch	Category I		
Lift capacity @ 24" behind pin	lbs. (kg)	670 (300)	
Steering	Hydrostatic Power Steering		
Tire size			
Front	Turf/Bar/Industrial	18 × 8.5–10 / 18 × 8.5–10 / 18 × 8.5–10	
Rear	Turf/Bar/Industrial	26 × 12–12 / 26 × 12–12 / 26 × 12–12	
Traveling speeds at rated engine rpm (Turf)			
Forward	mph (km/h)	0–8.4 (0–13.5)	
Reverse	mph (km/h)	0–6.2 (0–10.0)	
Dimensions			
Length with 3-point hitch	in. (mm)	95.5 (2425)	
Width (w/ turf tire)	in. (mm)	44.5 (1130)	
Height with ROPS	in. (mm)	70.4 (1787)	
Wheelbase	in. (mm)	55.1 (1400)	
Ground clearance (front axle)	in. (mm)	8.7 (220)	
Tread	Front	in. (mm)	36.6 (930)
	Rear	in. (mm)	32.2 (820)
Turning radius (w/o brake)	feet (m)	7.5 (2.3)	
Tractor weight	lbs. (kg)	1389 (630)	

Loader Specifications

Model	LA243	
Lift capacity (500mm fwd, max. height)	lbs. (kg)	518 (235)
Lift capacity (pivot pin, max height)	lbs. (kg)	745 (338)
Max. lift height (to bucket pivot pin)	in. (mm)	71.3 (1810)
Dumping clearance	in. (mm)	52.4 (1330)
Dumping reach at max. lift height	in. (mm)	28.9 (735)
Maximum dump angle	degrees	45
Reach with bucket on ground	in. (mm)	54.7 (1390)
Bucket rollback angle	degrees	29
Digging depth	in. (mm)	4.7 (120)
Bucket width	in.	48
Breakout force (500mm fwd)	lbs. (N)	992 (4410)
Raising time / lowering time (w/o load)	second	3.5 / 2.7
Bucket rollback time / dumping time	second	2.4 / 1.7

Mid-Mount Mower Specifications

Model	RCK54-23BX	RCK54P23BX	RCK60B23BX
Type	Side discharge		
Number of blades	3		
Mounting method	Suspended-Linkage	Self Balance	
Cutting width	in. (mm)	54 (1372)	60 (1524)
Cutting height	in. (mm)	1.0–4.0 (25–102)	
Adjustment of cutting height	Dial gauge		
Weight	lbs. (kg)	189 (86)	209 (95) / 250 (115)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.