



**Specifications**

MODEL		F2680E (2WD)	F3080 (4WD)	F3680 (4WD)		
Engine	Model	Kubota D1105	Kubota D1305	Kubota V1505		
	Type	Liquid-cooled diesel (3 cyl)			Liquid-cooled diesel (4 cyl)	
	Maximum horsepower	HP	25.5	30	36	
	Total displacement	cu. in. (cm <sup>3</sup> )	68.6 (1,123)	77.0 (1,262)	91.5 (1,498)	
	Air cleaner (type)		Dual element			
	Air restriction indicator		N/A		Standard	
	Alternator		12V, 40A			
	Fuel Tank Capacity	U.S. gal. (l)	16.1 (61.0)			
Transmission/ Drive Train	Type	Hydrostatic (HST) (F2/R2)				
	Traveling Speed (Forward/Reverse)	mph (km/h)	0 - 12.5 (20) / 0 - 6.8 (11)			
	4WD mode select	N/A	4WD Full-time, Auto-assist 4WD (forward/reverse)			
	Steering	Hydrostatic power steering / tilt wheel				
	Turn Assist Brake	Optional				
	Cruise control	Optional				
	Brakes	Wet discs				
	Differential lock	Standard				
Dimensions & Weight	Overall Length (tractor only)	in. (mm)	94.8 (2,408)			
	Overall Width (tractor only)	in. (mm)	56.4 (1,433)			
	Overall Height w/ ROPS upright	in. (mm)	79.4 (2,017)			
	Weight (w/o mower deck)	lbs. (kg)	1,488 (675)	1,541 (699)	1,581 (717)	
	Tire size	Front	23x10.5-12		24x12-12	
		Rear	16x6.5-8		18x9.5-8	
	Tire tread (front/rear)	in. (mm)	38.4 (975) / 34.2 (870)		41.8 (1,063) / 41.1 (1,045)	
	Wheelbase	in. (mm)	52.0 (1,321)			
Mower Mounting	Ground clearance	in. (mm)	7.4 (188)			
	Clutch type		Wet multi disc, hydraulic			
	PTO revolution	rpm	2,545			
	Lift system		Hydraulic, 2-point hitch			
	Deck tilt angle		90 degrees			
	Deck tilt-assist mechanism		Standard on 72" decks			
	Weight transfer		Standard			
Other Features	Seat	Deluxe seat w/4 adjustable controls (weight,lumbar, back angle, arm rests)				
	Fuel gauge	Electric meter				
	Tachometer	Optional				
	Tool box	Standard				
	Cup holder	Standard				
	Operator Presence Control	Standard				
	Foldable ROPS	Standard				
MOWER MODELS		RCK60P-F36	RCK72P-F36	RCK60R-F36	RCK72R-F36	
Specifications	Discharge	Side discharge		Rear discharge		
	Cutting width	in. (mm)	60 (1,520)	72 (1,826)	60 (1,520)	72 (1,826)
	Cutting height	in. (mm)	1 - 5 (25-127)			
	Cutting height adjustment	in. (mm)	Each 0.25 (6.4)			
	Deck depth	in. (mm)	5.5 (140)			
	Deck pan		Welded			
	Deck thickness	in. (mm)	0.18 (4.5)			
	Number of blades		3			
	Front baffle kit (manicured finish)		Optional		N/A	
	Mulching kit (mulch cut)		Optional			
	Mowing rate at 7 mph		3.6 acres/hour	4.3 acres/hour	3.6 acres/hour	4.3 acres/hour

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

