



**G Garden Tractors**  
**G2160/G2460G/G2160-R48S**



**SPECIFICATIONS**

MODEL		G2160	G2160-R48S	G2460G	
Engine	Type	Liquid-cooled Kubota diesel		Liquid-cooled Kubota gas	
	No. of cylinders	3			
	Total displacement	cu. In. (cm <sup>3</sup> )	47.7 (778)	45.1 (740)	
	Max. Horsepower	HP	21	24	
	Battery Voltage		12V, 450 CCA	12V, 300 CCA	
	Fuel Tank Capacity	gal. (l)	5.8 (22.0)		
Dimensions & Weight	Length (tractor only)	in. (mm)	G2160 74.2 (1885) G2160-R48S 115.3 (2928)	74.2 (1885)	
	Overall Width (tractor only)	in. (mm)	42.3 (1075)		
	Overall Width (with 48" mower)	in. (mm)	50.3 (1277)		
	Overall Width (with 54" mower)	in. (mm)	66.5 (1690)		
	Overall Width (with 60" mower)	in. (mm)	72.6 (1843)		
	Max. Overall Height	in. (mm)	50.4 (1280)		
	Turning Radius (inside rear tire)	ft. (m)	28.0 (711) Left Turn		
	Uncut grass radius w/ 48" mower	in. (m)	27.0 (685) Left or Right Side		
		w/ 54" mower	in. (m)	25.0 (635) Left Side	
		w/ 60" mower	in. (m)	23.5 (597) Left Side	
	Weight (w/out Mower Deck)	lbs. (kg)	860 (390)	2346 (560)	860 (390)
	Wheelbase	in. (mm)	50.8 (1290)		
	Wheel Tread (Front/Rear)	in. (mm)	32.5 (825) / 30.7 (780)		
Tire Size	Front/Rear	16 x 6.50 - 8 / 23 x 10.50 - 12			
Transmission/ Drive Train	Steering System	Electronic rack-and-pinion power steering			
	Traveling Speed (Forward/Reverse)	mph (km/h)	0 - 9.3 (0 - 15.0) / 0 - 3.8 (0 - 6.0)		
	Transmission	Hydrostatic transmission			
	Clutch	Direct shaft drive			
	Brake	Internal expanding shoe			
Other Performance Features	Grass Catcher Type	Power Flow (Opt.)	Direct shoot (Std.)	Power flow (Opt.)	
	Capacity	bushels	9.75	14.2	9.75
	Seat Adjustment	One touch system with seat suspension			
	Step Deck	Full flat			
	KRA (Kubota Reverse Awareness System)	Standard			

Model		RCK48R-21G	RCK54-24G	RCK60B-24G	
Mower	Attachment	Quick Attach with over center lever			
	Adjustment of Cutting height	Dial gauge			
	Cutting Width	in. (mm)	48 (1219)	54 (1372)	60 (1524)
	Cutting Height	in. (mm)	1.0 - 4.0 (25 - 102) in 1/2" increments		
	Number of Blades		3		
	Discharge		Right side		

All standard equipment in base model machines except where noted.  
 The company reserves the right to change the above specifications without notice.  
 These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

