

Kubota



Compact Tractors

L3130



COMPARISON

FEATURE	KUBOTA		JOHN DEERE	NEW HOLLAND
	L3130		3320	TC29DA
Engine				
Engine Manufacturer/Model		Kubota D1503	Yanmar 3TNV88	Shibaura
Gross Horsepower	HP	32.1	32.5	29
PTO Horsepower	HP	25.5 Gear or 24.0 Hydro	25.5 Gear or 25.0 Hydro	25 Gear or 23.6 Hydro
Rated Speed	RPM	2700	2600	2800
No. Cylinders/Displacement	cu. in.	3 / 91.5	3 / 100	3 / 81.2
Fuel Tank Capacity	gal.	10.6	13.5	7.3
Air Cleaner		Dual Element	Dual Element	Dual Element
Dimensions				
Wheelbase	in.	71.1	68	63
Overall Length (w/out 3-pt hitch)	in.	114.8	Info Not Available	106.2 (w/ 3-pt hitch)
Overall Width (min. tread)	in.	59.8	Info Not Available	54.3
Overall Height (top of ROPS)	in.	84.3	Info Not Available	87.8
Weight (inc. std. tires and ROPS)	lbs.	3220 Gear or 3305 Hydro	2900	2440 Gear or 2474 Hydro
Min. Ground Clearance	in.	14.0	Info Not Available	Info N/A
Transmission / Drive Train				
Transmission		Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic	Collar Shift or Hydrostatic
Manual Speeds		8F/8R Gear, 12F/8R, or 3 Range Hydro	12F/12R Gear or 3 Range Hydro	9F/3R or 3 Range Hydro
Creep Speed		Optional (Gear-Drive Only)	Not Available	Not Available
Brakes		Multiple Wet Disc	Wet Disc	Wet Disc
Clutch		Dry Type - Single Stage	Wet Disc	Info N/A
PTO System				
Type		Independent	Independent	Live
Rear PTO	RPM	540	540	540
Mid PTO	RPM	Optional 2000	Optional 2100	Opt (Gear) / Std (Hydro) 2000




Compact Tractors

L3130



COMPARISON

FEATURE	KUBOTA		JOHN DEERE	NEW HOLLAND
	L3130		3320	TC29DA
Hydraulic System / 3-Point Hitch				
Hitch Category (SAE)		Category I	Category I	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers Only	Telescopic Stabilizers and Flexible Link Ends
Pump Capacity (Main/PS)	gpm	8.3 / 4.9	8.6 / 5.3	7.6 / 5.1
Lift Capacity at 24" Behind L.P.	lbs.	2650	2200	1635
Draft Control/Top-n-Tilt Kit		Optional / Optional	Not Available / Optional	Not Available
Steering		Hydrostatic	Hydrostatic	Hydrostatic
Standard Tires				
Front Tire		7.2-16	7-14	7-14
Rear Tire		12.4-24	11.2-24	11.2-24
Other Specifications				
Deck		Flat	Flat	Semi-Flat
Min. Turning Radius	ft.	8.9	8.8	Info N/A
Cruise Control		Standard (Hydro Only)	Optional	Standard (Hydro Only)
Alternator	amps	40 (60 on Cab Models)	40	40
Rear Differential Lock		Standard	Standard	Standard
Entry/Exit Step		Standard	Standard	Optional
Drawbar		Adj. Drawbar Std/Swinging Optional	Adjustable Drawbar	Swinging
Foldable ROPS		Optional (No Charge)	Standard	Standard
Tilt Steering Wheel		Standard	Standard	Standard
Tool Box		Standard	Standard	Standard
Cup Holder		Standard	Standard	N/A
Deluxe Seat with Armrests		Standard	Armrests Optional	Armrests Optional
Rubber Mat		Standard	Standard	Standard
Underhood Muffler		Standard	Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.