



COMPARISON

FEATURE		KUBOTA L3830	JOHN DEERE 3520	NEW HOLLAND TC35A/DA
Engine				
Engine Manufacturer/Model		Kubota D1803	Yanmar 3TNV84T	Shibaura
Gross Horsepower	HP	39	37	35
PTO Horsepower	HP	32.0 Gear or 30.5 Hydro	30.5 Gear or 30.0 Hydro	29.6 Gear or 29.1 Hydro
Rated Speed	RPM	2700	2600	2600
No. Cylinders/Displacement	cu. in.	3 / 111.4	3 / 91.5	3 / 101.1
Fuel Tank Capacity	gal.	10.6	13.5	13
Air Cleaner		Dual Element	Dual Element	Dual Element
Dimensions				
Wheelbase	in.	72.4	68	73.5
Overall Length (w/out 3-pt hitch)	in.	117.5	Info Not Available	125.2 (w/ 3-pt hitch)
Overall Width (min. tread)	in.	66.5	Info Not Available	66.6
Overall Height (top of ROPS)	in.	84.8	Info Not Available	95.5
Weight (inc. std. tires and ROPS)	lbs.	3260 Gear or 3340 Hydro	2900	3009 (2WD), 3096 (4WD) or 3252 (Hydro)
Min. Ground Clearance	in.	14.6	Info Not Available	Info N/A
Transmission / Drive Train				
Transmission		Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic
Manual Speeds		8F/8R Gear, 12F/8R, or 3 Range Hydro	12F/12R Gear or 3 Range Hydro	12F/12R or 4 Range Hydro
Creep Speed		Optional (Gear-Drive Only)	Not Available	N/A
Brakes		Multiple Wet Disc	Wet Disc	Wet Disc
Clutch		Dry Type - Single Stage	Wet Disc	Info N/A
PTO System				
Type		Independent	Independent	Independent
Rear PTO	RPM	540	540	540
Mid PTO	RPM	Optional 2000	Optional 2100	N/A (Gear) / Opt (Hydro) 2000



COMPARISON

FEATURE		KUBOTA L3830	JOHN DEERE 3520	NEW HOLLAND TC35A/DA
Hydraulic System / 3-Point Hitch				
Hitch Category (SAE)		Category I	Category I	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers Only	Telescopic Stabilizers and Flexible Lower Links (Standard (DA) / Optional (A))
Pump Capacity (Main/PS)	gpm	8.3 / 4.9	8.6 / 5.3	9.8 / 5.1
Lift Capacity at 24" Behind L.P.	lbs.	2760	2200	2025
Draft Control/Top-n-Tilt Kit		Optional / Optional	Not Available / Optional	Optional / N/A
Steering		Hydrostatic	Power	Hydrostatic
Standard Tires				
Front Tire		8.3-16	7-14	5.5-16 / 7-16
Rear Tire		14.9-24	11.2-24	13.6-24
Other Specifications				
Deck		Flat	Flat	Semi-Flat
Min. Turning Radius	ft.	9.5	8.8	Info N/A
Cruise Control		Standard (Hydro Only)	Optional	Standard (Hydro Only)
Alternator	amps	40 (60 on Cab Models)	40	40
Rear Differential Lock		Standard	Standard	Standard
Entry/Exit Step		Standard	Standard	Left and Right Standard (Right- Hand Step N/A on A models)
Drawbar		Adj. Drawbar Std/Swinging Optional	Adjustable Drawbar	Swinging
Foldable ROPS		Optional (No Charge)	Standard	Standard
Tilt Steering Wheel		Standard	Standard	Standard (DA) / N/A (A)
Tool Box		Standard	Standard	Standard (DA)/Optional (A)
Cup Holder		Standard	Standard	Standard(DA)/Optional (A)
Deluxe Seat with Armrests		Standard	Armrests Optional	Armrests Optional (DA)/N/A (A)
Rubber Mat		Standard	Standard	Standard
Underhood Muffler		Standard	Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.