




**COMPARISON**

FEATURE		KUBOTA L4330	JOHN DEERE 3720	JOHN DEERE 4120	NEW HOLLAND TC40A/DA
<b>Engine</b>					
Engine Manufacturer/Model		Kubota V2203	Yanmar 3TNV84HT	JD4024T	Shibaura
Gross Horsepower	HP	43.2	44.0	43.0	40
PTO Horsepower	HP	36.0 Gear or 34.5 Hydro	35.0	35.5 GR/ 35.0 HYD	35 Gear or 33.2 Hydro
Rated Speed	RPM	2600	2600	2400	2600
No. Cylinders/Displacement	cu. in.	4 / 134.1	3 / 101.1	4 / 149	4 / 121.7
Fuel Tank Capacity	gal.	10.6	13.5	14.5	13
Air Cleaner		Dual Element	Dual Element	Dual Element	Dual Element
<b>Dimensions</b>					
Wheelbase	in.	74.6	68	71.5	73.5
Overall Length (w/out 3-pt hitch)	in.	121.2	Info N/A	Info N/A	125.2 (w/ 3-pt hitch)
Overall Width (min. tread)	in.	66.5	Info N/A	Info N/A	66.6
Overall Height (top of ROPS)	in.	84.8	Info N/A	Info N/A	95.5
Weight (inc. std. tires and ROPS)	lbs.	3440 Gear or 3515 Hydro	2900	3700	3300 Gear or 3328 Hydro
Min. Ground Clearance	in.	14.6	Info N/A	Info N/A	Info N/A
<b>Transmission / Drive Train</b>					
Transmission		Synchronized Shuttle or Hydrostatic	Hydrostatic Only	Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic
Manual Speeds		8F/8R Gear, 12F/8R, or 3 Range Hydro	3 Range	12F/12R Gear or 3 Range Hydro	12F/12R or 4 Range Hydro
Creep Speed		Optional (Gear-Drive Only)	Not Available	Not Available	N/A
Brakes		Multiple Wet Disc	Wet Disc	Wet Disc	Wet Disc
Clutch		Dry Type - Single Stage	Not Available	Wet Disc	Info N/A
<b>PTO System</b>					
Type		Independent	Independent	Independent	Independent
Rear PTO	RPM	540	540	540	540
Mid PTO	RPM	Optional 2000	Optional 2100	Optional 2100	N/A (Gear) / Opt (Hydro) 2000





Compact Tractors

L4330



### COMPARISON

FEATURE		KUBOTA L4330	JOHN DEERE 3720	JOHN DEERE 4120	NEW HOLLAND TC40A/DA
<b>Hydraulic System / 3-Point Hitch</b>					
Hitch Category (SAE)		Category I	Category I	Category I	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers	Telescopic Stabilizers	Telescopic Stabilizers and Flexible Lower Links (Standard (DA) / Optional (A))
Pump Capacity (Main/PS)	gpm	9.4 / 4.7	8.6 / 5.3	12 / 5.1	9.8 / 5.1
Lift Capacity at 24" Behind L.P.	lbs.	2760	2200	2500	2330
Draft Control/Top-n-Tilt Kit		Optional / Optional	Not Available/Optional	Not Available/Optional	Optional / N/A
Steering		Hydrostatic	Power	Power	Hydrostatic Power Steering
<b>Standard Tires</b>					
Front Tire		8.3-16	7-14	8-16	7-16
Rear Tire		14.9-24	11.2-24	13.6-28	13.6-24
<b>Other Specifications</b>					
Deck		Flat	Flat	Flat	Semi-Flat
Min. Turning Radius	ft.	8.9	8.8	8.8	Info N/A
Cruise Control		Standard (Hydro Only)	Optional	Not Available	Standard (Hydro Only)
Alternator	amps	40 (60 on Cab Models)	40	75	40
Rear Differential Lock		Standard	Standard	Standard	Standard
Entry/Exit Step		Standard	Standard	Standard	Left and Right Standard (Right-Hand Step N/A on A models)
Drawbar		Adj. Drawbar Std/Swinging Optional	Adjustable Drawbar	Adjustable Drawbar	Swinging
Foldable ROPS		Optional (No Charge)	Standard	Standard	Standard
Tilt Steering Wheel		Standard	Standard	Standard	Standard (DA) / N/A (A)
Tool Box		Standard	Standard	Standard	Standard (DA) / Optional (A)
Cup Holder		Standard	Standard	Standard	Standard (DA) / Optional (A)
Deluxe Seat with Armrests		Standard	Armrests Optional	Armrests Optional	Armrests Optional (DA)/N/A (A)
Rubber Mat		Standard	Standard	Standard	Standard
Underhood Muffler		Standard	Standard	Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.