




COMPARISON

| FEATURE | | KUBOTA L4630 | JOHN DEERE 4320 | NEW HOLLAND TC45A/DA | NEW HOLLAND TC48DA |
|-----------------------------------|---------|--------------------------------------|-------------------------------------|-------------------------------------|-----------------------|
| Engine | | | | | |
| Engine Manufacturer/Model | | Kubota V2203 | JD 4024T | Shibaura | Shibaura |
| Gross Horsepower | HP | 47.2 | 48.0 | 45 | 48 |
| PTO Horsepower | HP | 39.5 Gear or 38.0 Hydro | 40.5 Gear or 40 Hydro | 39.6 Gear or 37.8 Hydro | 40 |
| Rated Speed | RPM | 2700 | 2400 | 2600 | 2800 |
| No. Cylinders/Displacement | cu. in. | 4 / 134.1 | 4 / 149 | 4 / 135.2 | 4 / 135.2 |
| Fuel Tank Capacity | gal. | 10.6 | 14.5 | 13 | 13.5 |
| Air Cleaner | | Dual Element | Dual Element | Dual Element | Dual Element |
| Dimensions | | | | | |
| Wheelbase | in. | 74.6 | 71.5 | 73.5 | 74.8 |
| Overall Length (w/out 3-pt hitch) | in. | 121.2 | Info Not Available | 125.2 (w/ 3-pt hitch) | 137.3 (w/ 3pt hitch) |
| Overall Width (min. tread) | in. | 66.5 | Info Not Available | 66.6 | 64.4 |
| Overall Height (top of ROPS) | in. | 84.8 | Info Not Available | 95.5 | 95 |
| Weight (inc. std. tires and ROPS) | lbs. | 3440 Gear or 3515 Hydro | 3700 | 3349 Gear or 3633 Hydro | 3976 |
| Min. Ground Clearance | in. | 14.6 | Info Not Available | Info N/A | Info N/A |
| Transmission / Drive Train | | | | | |
| Transmission | | Synchronized Shuttle or Hydrostatic | Synchronized Shuttle or Hydrostatic | Synchronized Shuttle or Hydrostatic | Synchronized Shuttle |
| Manual Speeds | | 8F/8R Gear, 12F/8R, or 3 Range Hydro | 12F/12R Gear or 3 Range Hydro | 12F/12R or 4 Range Hydro | 12F / 12R |
| Creep Speed | | Optional (Gear-Drive Only) | Not Available | N/A | N/A |
| Brakes | | Multiple Wet Disc | Wet Disc | Wet Disc | Wet Disc |
| Clutch | | Dry Type - Single Stage | Wet Disc | Info N/A | Info N/A |
| PTO System | | | | | |
| Type | | Independent | Independent | Independent | Independent |
| Rear PTO | RPM | 540 | 540 | 540 | 540 |
| Mid PTO | RPM | Optional 2000 | Optional 2100 | N/A (Gear) / Opt (Hydro) 2000 | N/A |





COMPARISON

| FEATURE | | KUBOTA L4630 | JOHN DEERE 4320 | NEW HOLLAND TC45A/DA | NEW HOLLAND TC48DA |
|---|------|---|-----------------------------|--|---|
| Hydraulic System / 3-Point Hitch | | | | | |
| Hitch Category (SAE) | | Category I | Category I | Category I | Category I and II |
| 3-Point Linkage | | Telescopic Stabilizers AND Telescopic Lower Links | Telescopic Stabilizers Only | Telescopic Stabilizers and Flexible Lower Links (Std (DA) / Opt (A)) | Telescopic Stabilizers and Flexible Lower Links |
| Pump Capacity (Main/PS) | gpm | 9.8 / 4.9 | 12 / 5.1 | 9.8 / 5.1 | 12.03 / 5.52 |
| Lift Capacity at 24" Behind L.P. | lbs. | 2760 | 2500 | 2330 | 3465 |
| Draft Control/Top-n-Tilt Kit | | Optional / Optional | Not Available / Optional | Optional / N/A | Standard / N/A |
| Steering | | Hydrostatic | Power | Hydrostatic | Hydrostatic |
| Standard Tires | | | | | |
| Front Tire | | 8.3-16 | 8-16 | 7-16 | 8-16 |
| Rear Tire | | 14.9-24 | 13.6-28 | 13.6-24 | 14.9-24 |
| Other Specifications | | | | | |
| Deck | | Flat | Flat | Semi-Flat | Semi-Flat |
| Min. Turning Radius | ft. | 8.9 | 9.2 | Info N/A | Info N/A |
| Cruise Control | | Standard (Hydro Only) | Optional | Standard (Hydro Only) | N/A |
| Alternator | amps | 40 (60 on Cab Models) | 75 | 40 | 40 |
| Rear Differential Lock | | Standard | Standard | Standard | Standard |
| Entry/Exit Step | | Standard | Standard | Left and Right Standard (Right Step N/A on (A)) | Left Step Standard, Right Step Optional |
| Drawbar | | Adj. Drawbar Std/Swinging Optional | Adjustable Drawbar | Swinging | Swinging |
| Foldable ROPS | | Optional (No Charge) | Standard | Standard | Standard |
| Tilt Steering Wheel | | Standard | Standard | Standard (DA) / N/A (A) | Standard |
| Tool Box | | Standard | Standard | Std (DA) / Opt (A) | Standard |
| Cup Holder | | Standard | Standard | Std (DA) / Opt (A) | Standard |
| Deluxe Seat with Armrests | | Standard | Armrests Optional | Armrests Optional (DA) / N/A (A) | Armrests Optional |
| Rubber Mat | | Standard | Standard | Standard | Standard |
| Underhood Muffler | | Standard | Standard | Standard | Standard |

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.