



SPECIFICATIONS

MODEL		L4630			
		DT (4WD)	GST (4WD)	HST (4WD)	GSTC (4WD,CAB)
Engine	Type	E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel			
	Engine gross power	HP (kW)	47.2 (35.2)		
	Engine net power	HP (kW)	44.7 (33.5)		
	PTO power	HP (kW)	39.5 (29.6)	38.0 (28.5)	39.5 (29.6)
	No. of cylinders		4		
	Bore & stroke	in. (mm)	3.4 x 3.6 (87 x 92.4)		
	Total displace	cu.in. (cc)	134.1 (2197)		
	Rated speed	rpm	2700		
	Battery		80D 26R, 12V		
	Alternator		12V, 40A		12V, 60A
	Fuel tank capacity	US gal. (L)	10.6 (40)		
PTO	Rear PTO				
	Revolution	1 speed: 540 rpm			
	Type	Independent	Independent ^{*2)}	Independent	
	Mid PTO	Option			
Hydraulic	Revolution	1 speed: 2000 rpm			
	Lift control type: Position	Standard			
	Draft	Option			
	Implement pump	GPM (L/min.)	9.8 (37.0)		
	Power steering pump	GPM (L/min.)	4.9 (18.6)		
	Total hydraulic flow	GPM (L/min.)	14.7 (55.6)		
3-point hitch	Lift capacity at 24 in. behind lift point	lbs. (kg)	2760 (1250)		
			Category I		
Traveling System	Transmission	FST 8F/ 8R	GST 12F / 8R	HST (3 Ranges)	GST 24F / 16R
	Steering	Hydrostatic power steering			
	Brake	Wet disc type			
	Clutch	Dry type single stage			
Std. tire size *1)	Front	8.3 - 16			
	Rear	14.9 - 24			

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*1) Kubota offers several tire options.

*2) With Master Clutch.

*3) Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.

*4) Standard on L4630GSTC.



SPECIFICATIONS

MODEL		L4630				
		DT (4WD)	GST (4WD)	HST (4WD)	GSTC (4WD,CAB)	
Travel speeds	No. of speeds (at rated engine speed)	GST*3)		Optional creep speeds for GST*3)*4)		HST
	mph (km/h)	12 Forward / 8 Reverse		12 Forward /8 Reverse		3 Ranges
		Forward	Reverse	Forward	Reverse	Forward
	First	0.9 (1.5)	0.9 (1.5)	0.10 (0.17)	0.10 (0.16)	Low:
	Second	1.3 (2.1)	1.3 (2.2)	0.15 (0.24)	0.14 (0.23)	L: 0 (0) to 3.7 (5.9)
	Third	1.8 (3.0)	2.0 (3.3)	0.20 (0.32)	0.23 (0.37)	Medium:
	Fourth	2.1 (3.5)	3.0 (4.9)	0.24 (0.39)	0.34 (0.55)	M: 0 (0) to 7.1 (11.4)
	Fifth	2.6 (4.2)	4.5 (7.3)	0.29 (0.47)	0.50 (0.81)	High:
	Sixth	3.2 (5.2)	6.3 (10.2)	0.36 (0.57)	0.71 (1.15)	H: 0 (0) to 15.7 (25.4)
	Seventh	3.9 (6.3)	10.3 (16.6)	0.44 (0.71)	1.16 (1.86)	Reverse
	Eighth	4.7 (7.6)	15.2 (24.5)	0.53 (0.85)	1.71 (2.75)	Low:
	Ninth	5.5 (8.9)		0.62 (1.00)		L: 0 (0) to 3.3 (5.3)
	Tenth	6.7 (10.9)		0.75 (1.20)		Medium:
Eleventh	10.8 (17.4)		1.21 (1.95)		M: 0 (0) to 6.6 (10.7)	
Twelfth	15.9 (25.7)		1.79 (2.88)		High:	
					H: 0 (0) to 14.2 (22.8)	
Dimensions	Overall length (w/o 3P)	in. (mm)		121.3 (3080)		
	Overall width (min. tread)	in. (mm)		66.5 (1690)		
	Overall height (w/ROPS)	in. (mm)		91.1/84.8 (2315/2155)	87.0 (2210)	
	Wheelbase	in. (mm)		74.6 (1895)		
	Min. ground clearance	in. (mm)		14.8 (375)		
	Front Tread	(Front tire)	in. (mm)			
			51.2 (1300)			
Rear Tread	(Rear tire)	in. (mm)				
		50.6 (1285) 56.5 (1435) 60.2 (1530)				
Min. turning radius (w/brake, 4WD disengaged)	feet (m)		9.5 (2.9)			
Weight (with ROPS)	lbs. (kg)	3440 (1560)	3470 (1575)	3515 (1595)	3815 (1730)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*1) Kubota offers several tire options.

*2) With Master Clutch.

*3) Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.

*4) Standard on L4630GSTC.