



SPECIFICATIONS

MODEL		L5030			
		GST (4WD)	GST (4WD)	HST (4WD)	
Engine	Type	E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel			
	Engine gross power	HP (kW)	52.2 (38.9)		
	Engine net power	HP (kW)	50.0 (37.5)		
	PTO power	HP (kW)	44.0 (33.0)	42.5 (31.8)	
	No. of cylinders		4		
	Bore & stroke	in. (mm)	3.4 x 4.0 (87 x 102.4)		
	Total displace	cu.in. (cc)	148.6 (2434)		
	Rated speed	rpm	2700		
	Battery		80D 26R, 12V		
	Alternator		12V, 45A	12V, 60A	
	Fuel tank capacity	US gal. (L)	11.4 (43)		
PTO	Rear PTO				
	Revolution		1 speed: 540 rpm		
	Type	Independent	Independent ^{*2)}		
	Mid PTO		Option		
Hydraulic	Revolution		1 speed: 2000 rpm		
	Lift control type: Position		Standard		
	Draft		Option		
	Implement pump	GPM (L/min.)	9.8 (37.0)		
	Power steering pump	GPM (L/min.)	4.9 (18.6)		
	Total hydraulic flow	GPM (L/min.)	14.7 (55.6)		
Traveling System	3-point hitch		Category I & II		
	Lift capacity at 24 in. behind lift point	lbs. (kg)	2980 (1350)		
	Transmission		GST 12F / 8R	HST (3 Ranges)	
Std. tire size *1)	Steering		Hydrostatic power steering		
	Brake		Wet disc type		
	Clutch		Dry type single stage		
Std. tire size *1)	Front		9.5 - 16		
	Rear		14.9 - 26		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*1) Kubota offers several tire options.

*2) With Master Clutch.

*3) Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.



SPECIFICATIONS

MODEL		L5030							
		GST (4WD)		GST (4WD)		HST (4WD)			
Travel speeds	No. of speeds (at rated engine speed)	GST ^{*3)}		Optional creep speeds for GST ^{*3)}		HST			
	mph (km/h)	12 Forward / 8 Reverse		12 Forward /8 Reverse		3 Ranges			
		Forward	Reverse	Forward	Reverse	Forward			
	First	1.0 (1.6)	0.9 (1.5)	0.11 (0.17)	0.10 (0.17)	Low:			
	Second	1.4 (2.3)	1.3 (2.2)	0.15 (0.25)	0.15 (0.24)	L: 0 (0) to 3.8 (6.1)			
	Third	1.8 (3.0)	2.1 (3.5)	0.21 (0.33)	0.24 (0.38)	Medium:			
	Fourth	2.2 (3.6)	3.1 (5.1)	0.25 (0.40)	0.35 (0.57)	M: 0 (0) to 7.3 (11.8)			
	Fifth	2.7 (4.4)	4.6 (7.5)	0.31 (0.49)	0.52 (0.84)	High:			
	Sixth	3.3 (5.3)	6.6 (10.7)	0.37 (0.59)	0.74 (1.19)	H: 0 (0) to 16.2 (26.1)			
	Seventh	4.0 (6.5)	10.6 (17.1)	0.45 (0.73)	1.20 (1.93)	Reverse			
	Eighth	4.9 (7.8)	15.7 (25.4)	0.55 (0.88)	1.77 (2.85)	Low:			
	Ninth	5.7 (9.2)		0.64 (1.03)		L: 0 (0) to 3.4 (5.5)			
	Tenth	6.9 (11.1)		0.77 (1.24)		Medium:			
Eleventh	11.1(17.9)		1.26 (2.02)		M: 0 (0) to 6.6 (10.7)				
Twelfth	16.5 (26.6)		1.85 (2.98)		High:				
					H: 0 (0) to 14.6 (23.5)				
Dimensions	Overall length (w/o 3P)	in. (mm)		126.2 (3205)					
	Overall width (min. tread)	in. (mm)		67.3 (1710)					
	Overall height (w/ROPS)	in. (mm)		92.7 / 86.2 (2355 / 2190)		89.4 (2270)			
	Wheelbase	in. (mm)		75.4 (1915)					
	Min. ground clearance	in. (mm)		15.9 (405)					
	Front Tread	(Front tire)	in. (mm)		52.8 (1340)				
	Rear Tread	(Rear tire)	in. (mm)		52.2 (1325)		56.3 (1410)		
Min. turning radius (w/brake, 4WD disengaged)	feet (m)		9.8 (3.0)						
Weight (with ROPS)	lbs. (kg)		3705 (1680)		3745 (1700)		4090 (1855)		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*1) Kubota offers several tire options.

*2) With Master Clutch.

*3) Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.