


**Specifications**

| Model                |                           |                                   | GR2010   | GR2110                                   |
|----------------------|---------------------------|-----------------------------------|--|--|
| Engine               | Model                     |                                   | <b>GH630</b>                                   | <b>Kubota D782</b>                       |
|                      | Type                      |                                   | <b>2 cylinders, gasoline, air-cooled</b>       | <b>3 cylinders, diesel, water-cooled</b> |
|                      | Total displacement        | cu. in. (cc)                      | <b>38.1 (624)</b>                              | <b>47.7 (782)</b>                        |
|                      | Gross Horsepower          | HP(kW)                            | <b>20.0 (14.7)</b>                             | <b>21.0 (15.5)</b>                       |
|                      | Engine layout             |                                   | <b>Horizontal</b>                              |  |
|                      | Fuel tank capacity        | gal.(L)                           | <b>4.8 (18)</b>                                |  |
| Dimensions           | Overall length            | in. (mm)                          | <b>77.2 (1960)</b>                             |  |
|                      | Overall width (w/mower)   | in. (mm)                          | <b>60.4 (1535)</b>                             | <b>66.3 (1685)</b>                       |
|                      | Overall height            | in. (mm)                          | <b>48.4 (1230)</b>                             |  |
|                      | Wheelbase                 | in. (mm)                          | <b>50.4 (1280)</b>                             |  |
| Tread                | Front                     | in. (mm)                          | <b>32.5 (825)</b>                              |  |
|                      | Rear                      | in. (mm)                          | <b>31.5 (800)</b>                              |  |
| Weight               | (With mower)              | lbs. (kg)                         | <b>881 (400)</b>                               | <b>948 (430)</b>                         |
| Tire Size            | Front                     |                                   | <b>16x6.5 - 8</b>                              |  |
|                      | Rear                      |                                   | <b>23x10.50 - 12</b>                           |  |
| Features             | Transmission              |                                   | <b>Hydrostatic Transmission</b>                |  |
|                      | Transmission drive        |                                   | <b>Shaft drive</b>                             |  |
|                      | Speed control             |                                   | <b>Single foot pedal</b>                       |  |
|                      | Traveling Speed (Forward) | mph (km/h)                        | <b>0 - 6.2 (0 - 10.0)</b>                      |  |
|                      | Traveling Speed (Reverse) | mph (km/h)                        | <b>0 - 3.1 (0 - 5.0)</b>                       |  |
|                      | Brake                     |                                   | <b>Internal expanding brake</b>                |  |
|                      | PTO clutch                |                                   | <b>Mechanical wet multi discs</b>              |  |
|                      | Mower deck drive          |                                   | <b>U-joint shaft</b>                           |  |
|                      | Steering system           |                                   | <b>Glide Steer, hydrostatic power steering</b> |  |
|                      | Operator's deck           |                                   | <b>Flat</b>                                    |  |
|                      | Seat adjustment           |                                   | <b>Slide</b>                                   |  |
|                      | Seat suspension           |                                   | <b>Parallel linkage</b>                        |  |
|                      | Fuel gauge                |                                   | <b>Standard</b>                                |  |
|                      | Hour meter                |                                   | <b>Standard</b>                                |  |
|                      | Easy checker              |                                   | <b>Standard</b>                                |  |
| Mower OPC.           |                           | <b>Standard</b>                   |  |  |
| Travel OPC.          |                           | <b>Standard</b>                   |  |  |
| Blade shut off brake |                           | <b>Mechanical wet multi discs</b> |  |  |

**Mower Specifications**

|                             |          |                             |                  |
|-----------------------------|----------|-----------------------------|------------------|
| Cutting width               | in. (mm) | <b>48 (1219)</b>            | <b>54 (1372)</b> |
| Mower blade drive           |          | <b>Shaft drive</b>          |                  |
| Lifting device              |          | <b>Hydraulic</b>            |                  |
| Mower mounting method       |          | <b>Parallel linkage</b>     |                  |
| Cutting height              | in. (mm) | <b>1.0 - 4.0 (25 - 102)</b> |                  |
| Cutting height adjustment   |          | <b>Dial</b>                 |                  |
| Cutting height increments   | in.      | <b>1/4</b>                  |                  |
| Number of blades            |          | <b>3</b>                    |                  |
| Direction of discharge      |          | <b>Right side</b>           |                  |
| Mower deck ground clearance | in. (mm) | <b>5.5 (140)</b>            |                  |

