


SPECIFICATIONS

| MODEL | | M5040 | M6040 | M7040 | |
|------------------------|---------------------------------------|---|---|------------------------------------|------------------------|
| Engine | Model | KUBOTA-V3007-DI | | KUBOTA-V3307-DI | |
| | Type (Make: KUBOTA) | 4-cylinder in-line direct injected | | 4-cylinder in-line direct injected | |
| | SAE Net Power | HP (kW) | 50.5 (37.7) | 62.0 (46.3) | 67.0 (50.0) |
| | PTO horsepower | HP (kW) | 45.0 (33.6) | 55.0 (41.0) | 62.0 (46.3) |
| | Total Displacement | cu.in. (cc) | 186 (3053) | 203 (3331) | 203 (3331) |
| | Bore X Stroke | in. (mm) | 3.70 X 4.30 (94X110) | 3.70 X 4.70 (94X120) | 3.70 X 4.70 (94X120) |
| | Rated speed | rpm | 2600 | 2600 | 2600 |
| | Fuel tank capacity | gal. (l) | 18.5 (70) ROPS Models / 29.1 (110) CAB Models | | |
| | Alternator/Battery | | 45 Amps / 12V 900 CCA ROPS Models 60 Amps / 12V 900 CCA ROPS Models | | |
| | Air cleaner | | 8 in. dry, dual element | | |
| Muffler / Exhaust Pipe | | Left side of hood vertical / Underhood muffler ROPS Models | | | |
| Transmission | No. of speeds (Option) | Cassette Type creep speed 12F X 12R | | | |
| | Main gear shift | 4-speed main transmission, synchronized shift | | | |
| | Range gear shift | 2-speed High / Low Constant Mesh | | | |
| | Shuttle shift | Synchro-Shuttle standard 2wd & 4wd models Hydraulic-Shuttle Optional on CAB Models | | | |
| | Creep Speed (Cassette type, optional) | mph | 0.20, 0.29, 0.39, 0.63 | 0.21, 0.30, 0.40, 0.65 | 0.22, 0.31, 0.42, 0.68 |
| | Max. travel speed | mph | 17.4 | 18 | 18.7 |
| | Main clutch type/diameter | in. (mm) | Synchro Shuttle , cerametallic button dry clutch 10.8 (275) Hydraulic Shuttle = Multi-Plate wet disc clutch 6 disks, 4.9 (125) | | |
| | Brake type | | Mechanically operated wet disc brakes | | |
| PTO System | Front wheel drive system | Bevel gear type, with Easy-To-Shift 4wd engagement whiling rolling | | | |
| | PTO type | Live-Independent PTO, Hydraulically operated wet clutch, w/PTO brake | | | |
| Hydraulics | PTO Speed | 540 rpm (6 splines) standard | | | |
| | Pump flow (Hitch & remotes) | gpm (l/min) | 11.0 (41.6) | | |
| | Pump flow (Power steering) | gpm (l/min) | 6.1 (23.0) | | |
| | 3-point hitch (Category II) | | Telescopic lower link ends, Telescopic stabilizers | | |
| | Control system | | Mechanical position and mixed draft control, Top link draft sensing | | |
| | Lift capacity 24" behind lift point | lbs. (kg) | Standard 3307 (1500) | | |
| Steering | Remote valves | 1 standard (2nd or 3rd. Optional) | | | |
| | Steering | Hydrostatic power steering | | | |
| | Cab | Operator area | ISO-mounted flat deck, Hanging Pedals, Tilt steering wheel | | |
| Seat | | Reclining, fully adjustable; height, weight, fore & aft., arm rests, with retractable seat belt | | | |



SPECIFICATIONS


| MODEL | | M5040 | M6040 | M7040 |
|--------------------------|-------------------------------------|---|---------------------------|----------------------------|
| Cab (cont.) | Lighting | ROPS: 2 headlights, 2 corner lights, 2 tail lights, 2 frt. and 4 rear safety flashers CAB: 2 headlights, 2 corner lights, 2 tail lights, 2 frt. and 4 rear safety flashers 2 front worklights, 2 rear work lights. | | |
| | Standard Cab Features | Ultra Grand Cab has an arched Beam roof line, Heater/Air conditioner, Sun visor, Front wiper/washer, Beverage holder, 12V/30 amp 3-Pin Electric outlet, Tinted glass, 2 external mirrors, 3-Position switch for Interior light 7-pin Trailer electric outlet, Optional Air Ride seat suspension. | | |
| Dimensions & Weight | Wheelbase | 2wd Models: ROPS 82.1 (2085) Cab 84.4 (2145) 4wd Models: ROPS 80.7 (2250) Cab 83.1 (2110) | | |
| | Overall width (minimum) | 73.2 (1860) | | |
| | Overall length | 2wd 140.4 (3565) / 4wd 135.6 (3445) | | |
| | Overall height ROPS/CAB | 95.3 (2420) / 98.2 (2495) | 96.9 (2460) / 99.8 (2535) | 97.2 (2470) / 100.2 (2545) |
| | Crop clearance | 16.5 (420) | | 16.9 (430) |
| | Tread width Front 2WD | 56.7-72.4 (1440-1840) | | |
| | Tread width Front 4WD | 52.4-56.3 (1330-1430) | | 55.9-59.9 (1420-1520) |
| | Tread width Rear | 52.0-67.7 (1420-1720) | 55.9 - 67.7 (1420-1720) | |
| | Turning radius (w/o brake) | 2wd 11.2 (3.3) | | 4wd 11.8 (3.6) |
| | Weight (w/Standard tire/Steel dish) | 2wd 3748 (1700) 4wd 3968 (1800) | 3858 (1750) / 4079 (1850) | 4475 (2030) / 4608 (2090) |
| | Standard front tire | 6.50-16 2wd / 9.5-24 4wd | 7.50-16 2wd / 12.4-24 4wd | 7.50-16 2wd / 9.5-24 4wd |
| Standard rear tire | 14.9-28 | 16.9-28 | 16.9-30 | |
| Other optional equipment | | Front weight bumper (std 2wd) Front weights, Rear wheel weights, Drawbar clevis (hammerstrap), 2nd and 3rd remote valves, Cassette type Creep speed, Rear axle spacer kit, Cab Radio cassette or CD Player with 7-Channel weather band, Grill Guard, Down Exhaust, Deluxe canopy for ROPS Models. | | |

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

Not for sale in Nebraska



Smile
on my mac