

Specifications

Model		M9540 (2WD)	M9540 (4WD)
Engine		V3800-DI-T	
Type (Make: KUBOTA)		E-CDIS, Direct Injection	
No. of cylinders/Aspiration		4/Turbocharged	
Rated speed	rpm	2600	
Engine net power	HP (kW)	95 (70.8)	
PTO power	HP (kW)	84 (62.7)	
Total displacement	cu.in. (cc)	230 (3769)	
Fuel tank capacity	gal. (ℓ)	23.8 (90)	
Air cleaner		Dry, dual-element	
Alternator	Amp	45 (80A optional)	
Transmission			
No. of speeds		12 forward/12 reverse	
Main gear shift (8 speeds)		6/Fully synchronized	
Hydraulic-shuttle		Column-mounted lever	
Main clutch type		Hydraulic multi-plate wet disc	
Brake type		Hydraulic wet discs	
Mechanical differential lock		Rear mechanical standard	Rear mechanical standard & front Limited Slip Automatic Differential
PTO			
PTO type		Live-independent PTO, hydraulic PTO with PTO brake, wet discs	
Speed	rpm	540 (540/1000 optional)	
Hydraulics			
Pump capacity (3-point hitch)	gpm (ℓ/min.)	17.0 (64.3)	
3-point hitch		Telescopic lower link ends, Telescopic stabilizers	
Category		II	
Control system		Position, draft (top link sensing) & mix control	
Lift capacity at 24 in. behind lift point	lbs. (kgf)	4630 (2100) 7055 (3200) : OPT	
No. of standard remote valves		1 standard (2nd, 3rd & flow control valve optional)	
Other features			
4WD drive system		Bevel gear type	
Steering		Hydrostatic power steering	
Hood type		Full open hood, slanted, steel	
Deck type/Pedal type		Semi-flat deck with rubber mat/hanging pedals	
Panel type		Electronic	
Fender shape		Wide, Round	
Standard tire size	Front/Rear	27×9.5-15/16.9-24	9.5-20/16.9-24
Dimensions & weight^(*)			
Overall length	in. (mm)	153 (3885)	148 (3760)
Overall height ROPS raised/ROPS retracted	in. (mm)	90.6 (2300)/66.4 (1686)	
Overall width ^(*)	in. (mm)	77.5 (1969)	
Wheelbase	in. (mm)	88.6 (2250)	
Crop clearance (Front Axle)	in. (mm)	16.3 (415)	
Tread width	Front	TBA	59.8-63.8 (1520-1620)
	Rear	59.1-74.8 (1500-1900)	
Turning radius (w/o brake) 4WD	ft. (m)	-	13.9 (4.25) ^(*)
Tractor weight	lb. (kg)	4895 (2220)	5314 (2410)
Optional equipment		2nd/3rd remote valve (SCD), 2nd/3rd remote valve (FD), Flow control valve, 3PT high capacity lift cylinder, Dual speed PTO kit, Rear work light kit, Drawbar clevis, Front grille guard, Suitcase weights, Wheel weights, etc.	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Some of the items pictured in this brochure are optional, and not standard equipment. Please contact your local Kubota dealer for warranty and safety information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

For complete operational information, the operator's manual should be consulted.

Not for sale in Nebraska.

(*) All dimensions measured with standard tire. (**) At 72-inch rear tire tread. (***) 4WD engaged.

Smile
on my mac