

**SPECIFICATIONS**

MODEL		ZD321		ZD326		ZD331		
		ZD321N-54	ZD321-60	ZD326S	ZD326P	ZD331P-60	ZD331LP-72	
Engine	Model	Kubota D782		Kubota D1005		Kubota D1305		
	Type	Diesel, liquid-cooled (3 cyl.)						
	Max. Horsepower (Gross)	21 HP@3200rpm		26 HP@3200rpm		31 HP@3000rpm		
	Total Displacement cu.in. (cc)	47.48 (778)		61.08 (1001)		76.98 (1261)		
Starting System		Key switch - super glow						
Dimensions	Overall length	86.0 (2185)		87.4 (2220)		91.9 (2335)		
	overall width in.(mm)	(w/mower)	66.1 (1680)		75.2 (1910)		87.5 (2223)	
		(w/o mower)	53.7 (1365)		57.5 (1460)			
	overall height in.(mm)	(w/ROPS upright)			75.4 (1915)			
(w/ROPS folded)				61.2 (1555)				
Wheelbase		in. (mm)		55.5 (1410)		60.0 (1525)		
Tread	Front	in. (mm)		38.4 (975)		42.1 (1070)		
	Rear	in. (mm)		43.3 (1100)		45.3 (1150)		
Tire Size	Front	in. (mm)		15 x 6.0-6		15 x 6.0 - 6 Flat-Free		
	Rear	in. (mm)		26 x 10.5 - 12		26 x 12.0 - 12		
Weight with Mower		lbs. (kg)		1671 (758)		1700 (771)		
Transmission System				1757 (797)		1773 (804)		
Speed Control				1812 (822)		2-HST w/ Gear		
Travel Speed Range		mph (km/h)		0 - 9.4 (0 - 15.0)		0 - 10.6 (0 - 17.0)		
Brake Type				0 - 5.2 (0 - 8.3)		0 - 5.3 (0 - 8.5)		
PTO				Wet multi disks, foot operated				
Type				Shaft Drive				
Clutch Type				Wet Multi Disk				
PTO Brake				Wet Single Disk				
Mower Deck	Model	RCK54P-321Z	RCK60P-331Z	RCK60P-331Z	RCK60P-331Z	RCK72P-331Z		
	Mower Lift System	Hydraulic						
	Deck Type	Fabricated Deck						
	Deck Depth	in. (mm)		6.0 (152)		6.5 (165)		
	Deck Steel Thickness	in. (mm)		0.18 (4.6), 0.17 (4.2)				
	Anti-scalp Roller	Swivel						
	Cutting Width of Mower	in.		54		60		
	Number of Blades			3 Blades				
	Cutting Height	1 in. ~ 5 in. (in 1/4 in. increments)						
Mounting System of Mower	Parallel Linkage							
Blade Tip Speed (max.)			17200 FPM		18200 FPM			
Seat Adjustment			18200 FPM				18100 FPM	
Step Deck			One Touch System (Weight, Armrest, Reclining, and Lumbar Support)					
Engine Stop System			Full Flat					
Fuel Tank Capacity	gals (L)		Key Stop				12.9 (48.8)	
Battery			12 Volts, 51R, 450CAA@0 degrees F, 70 min. RC.					
Alternator Capacity			14 Volts 14 Amps					
Water Temperature Indicator			Standard					
Hour Meter			Standard					
Fuel Gauge			Electric					

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all