


SPECIFICATIONS

MODEL		ZG20-48	ZG23-54	
Engine	Type	OHV Gasoline Air cooled		
	No. of cylinders	2		
	Total displacement	38.1 (624)	41.1 (674)	
	Gross power	20	23 (17.1)	
	Battery Voltage	12 V		
	Fuel Tank Capacity	6.1 (23.0)		
Dimensions & Weight	Overall Length	76.8 (1950)		
	Overall Width (tractor only)	60.4 (1535)	66.3 (1685)	
	Overall Height with ROPS upright	70.1 (1780)		
	Weight (w/ Mower Deck)	1058 (480)	1102 (500)	
	Wheelbase	46.7 (1185)		
	Wheel Tread	33.9 (860)		
	Tire Size	13 x 5.0 - 6 / 23 x 10.5 - 12		
Transmission/ Drive Train	Steering System	Manual gear / sector		
	No. of speeds	Infinite to maximum		
	Traveling Speed	mph (km/h)	0 - 9.0 (0 - 14.5)	
		Forward	0 - 5.0 (0 - 8.0)	
	Reverse			
	Break Type	Wet multi disc		
	Transmission	2-HST w/Gear		
	Speed control	2-hand lever		
PTO Type	Shaft Drive			

MODEL		RCK48P-20ZG	RCK54P-23ZG
Mower Specifications	Mower lift system	Foot operated hydraulic	
	Deck Depth	5.1 (130)	
	Mounting System of Power	Parallel linkage	
	Blade Drive Method	Heavy duty belt system	
	Adjustment of Cutting height	Dial type adjustment	
	Cutting Width	48 (1219)	54 (1372)
	Cutting Height	1.0 - 5.0 in 1/4" increments	
	Number of Blades	3	
	Blade Tip Speed (max.)	15,800 fpm	16,000 fpm
	Mulching Kit	ZG3049	ZG3059
	Grass Catcher		GCK54-23Z

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.



Smile
on my mac